



**SPECIFICATION**

Model NO.	LICG24HTC100B	LICG24AD100V	LICG24AD100A	LICG24HTC130S	LICG24HTC130J	LICG24HTC200F	LICG24HTC200NA	LICG24HTC200NS	LICG24HTC200FV	LICG24HTC200EP	LICG24AD300NA	LICG24AD400V
Video Output Mode	AHD/CVI/TVI/CVBS	AHD	AHD/CVBS	AHD/CVI/TVI/CVBS	AHD/CVI/TVI/CVBS	AHD/CVI/TVI/CVBS	AHD/CVI/TVI/CVBS	AHD/CVI/TVI/CVBS	AHD/CVI/TVI/CVBS	AHD/CVI/TVI/CVBS	AHD/TVI	AHD

**Camera**

Image Sensor	OV9732	OV9732	AR0141	IMX225	S3130	F22	AR0237	IMX323	OV2718	MN34227	AR0330	OV4689
DSP	HTC960E	NVP2431H	HTC960	HTC960E	HTC960E	HTC1080E	NVP2441H	NVP2441H	HTC1080E	HTC1088	NVP2470H	NVP2475H
Image Resolution	720P	720P	720P / 960H	960P / 960H	1080P / 960H	1080P	1080P / 960H	1080P / 960H	1080P / 960H	1080P / 960H	3MP / 960H	4MP
Effective Pixels	1280*720	1280*720	1280*720	1280*960	1280*960	1920*1080	1920*1080	1920*1080	1920*1080	1920*1080	1920*1536	2560*1440
TV System	PAL/NTSC											
Electronic Shutter	1/25s~1/50,000s , 1/30s~1/60,000s											
S/N Ratio	≥50dB											
Scanning System	Progressive Scan											

**Lens**

Focus Length	3.6mm	3.6mm	3.6mm	3.6mm	3.6mm	3.6mm	3.6mm	3.6mm	3.6mm	3.6mm	3.6mm	3.6mm
Focus Control	Fixed	Fixed	Fixed	Fixed	Fixed	Fixed	Fixed	Fixed	Fixed	Fixed	Fixed	Fixed
Lens Type	Fixed	Fixed	Fixed	Fixed	Fixed	Fixed	Fixed	Fixed	Fixed	Fixed	Fixed	Fixed
Pixels	2M Pixels	2M Pixels	2M Pixels	2M Pixels	2M Pixels	2M Pixels	3M Pixels	3M Pixels	3M Pixels	3M Pixels	3M Pixels	5M Pixels
Auto Iris Support	NO	NO	NO	NO	NO	NO	NO	NO	NO	NO	NO	NO

**Night Vision**

Infrared LED	14μ x 18PCS											
Infrared Distance	20M											
IR Status	Under 10 Lux by CDS											
IR Power On	CDS Auto Control											

**Camera Features**

Day/Night	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES
OSD Menu Language	YES	NO	NO	YES	YES	YES	YES	YES	YES	YES	YES	YES
White Balance	AUTO / MANUAL	AUTO	AUTO	AUTO / MANUAL	AUTO / MANUAL	AUTO / MANUAL	AUTO / MANUAL	AUTO / MANUAL	AUTO / MANUAL	AUTO / MANUAL	AUTO / MANUAL	AUTO / MANUAL
Gain Control	AUTO	AUTO	AUTO	AUTO	AUTO	AUTO	AUTO	AUTO	AUTO	AUTO	AUTO	AUTO
Noise Reduction	DNR	3DNR	DNR	DNR	DNR	DNR	3DNR	3DNR	DNR	3DNR	DNR	DNR
Picture Adjustment	YES	NO	NO	YES	YES	YES	YES	YES	YES	YES	YES	YES
WDR	YES	NO	NO	YES	YES	YES	YES	YES	YES	YES	YES	YES
OSD Support	YES	NO	NO	YES	YES	YES	YES	YES	YES	YES	YES	YES
UTC	YES	NO	NO	YES	YES	YES	YES	YES	YES	YES	YES	YES

**General**

Housing	Metal, IP66											
Bracket	YES											
Dual Voltage	NO											
IR Cut Filter	YES											
Heater	NO											
Operation Temperature	-10℃ ~ +50℃ RH95% Max											
Storage Temperature	-20℃ ~ +60℃ RH95% Max											
Power Source	DC12V±10%, 500mA											
Dimension	168(W) x 73.5(H) x 65(D)mm											
Weight	500g											